



NEW BUILD



TYPICAL USES

- Moisture barrier for new unfinished construction material to prevent moisture uptake
- Suitable as a primer coat

WAYS TO APPLY

- Airless Sprayer (0.015 spray tip)
- Roller / Brush

PRECAUTIONS

- Appropriate for new unfinished building materials
- Not appropriate for application to exterior surfaces
- Do not allow to freeze
- Completely review the SDS and Product Label prior to use

HOW IT WORKS

- The newBuild coating is a latex based coating that contains nano-silver.
- The coating provides a moisture barrier to reduce moisture uptake of the substrate.
- Silver is a natural antimicrobial.

APPLICATION

- In order to achieve the best results, Anabec recommends spot cleaning building materials with obvious mold stains, dirt and debris with Anabec's Advanced Cleaning Solution.
- Allow building materials to fully dry prior to application of coating. Moisture content of the building material should be 16-20%.
- Prior to product use mix thoroughly using a powered paddle mixer. Mixing times may vary based on mixer power and product settling.
- If adding any tint, do so during the mixing process and mix thoroughly to ensure color consistency.
- For best results apply with an Airless Paint Sprayer using tip size 0.015. Product gets an estimated 800-1000 square foot per gallon of coverage, based on substrate profile.
- When applying with brush / roller coverage may be less.
- Product is dry to touch in 30-60 minutes, completely dry in 18-24 hours.
- Clean up equipment with soap and water.